

ENCLOSED 5 / 6-WIDE ATV

STANDARD FEATURES

- All-Aluminum Construction, Integrated Design
- 16" O/C Wall Studs
- 24" O/C Floor & Roof Studs
- 2"x3" Subframe Tubing
- 5/8" Water Resistant Decking
- Torsion Axle
- Screwless .030" Bonded Side Panels
- One-Piece Seamless Aluminum Roof
- LED Lighting
- V-Nose Design (24")
 - 2000# Center Jack w/ Foot (1200# on 5 Wide)
- 3" Exterior Trim
- Luan Interior Walls (5 Wide)
- 3/8" WR Interior Walls (6 Wide)
- Rear Ramp w/Spring Assist
- 12" Bright Stoneguard
- Plastic Salem Vents
- 1 Interior Dome Light w/Wall Switch (W-S 6' Wides only)
- Polished Aluminum Fenders
- 32"x66" Paddle Handle Door
(Optional on 5-Wide)
- 2 Rows of slide track w/ 4 sliding d-rings
- (2) 5000# Safety Chains
- 3500# Coupler w/ 2" Ball
- 12v Wall Switch (Optional on 5 wide)
- 4-Way Flat Power Connection
- Limited 4-Year Warranty

STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	PC5x8-IF	PC6x10-IF	PC6x12-IF
Box WxLxH	60"x8"x66"	72"x10"x81"	72"x12"x81"
Interior WxLxH	57.5"x7'9"x64"	69.5"x9'9"x79"	69.5"x11'9"x79"
Overall WxLxH	80"x12'4"x84"	94"x14'4"x99"	80"x16'4"x99"
Deck Height	18"	18"	18"
Rear Door Opening WxH	52"x62"	64"x75"	64"x75"
Axle(s) - Qty/Rating	1-2200#	1-3500#	1-3500#
Wheels	15" Silver Mods	15" Silver Mods	15" Silver Mods
Tires	205/75R15	205/75R15	205/75R15
GVWR	2200#	2990#	2990#
Curb Weight	830#	905#	955#
Payload	1370#	2085#	2035#
Hitch Height	17"	17"	17"