

## ENCLOSED INLINE SNOW [ INTEGRATED FRAME ELITE ]

### STANDARD FEATURES

- All-Aluminum Construction
- Integrated Frame Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x4" Subframe Tubing
- 5/8" Water Resistant Decking
- Leaf Spring Suspension (4" Drop)
- One-Piece Seamless Aluminum Roof
- 12" Water Resistant Kickplate
- White Vinyl Backed Luan Walls
- Recessed LED Exterior Lighting
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door w/ Spring Assist
- V-Nose Design (60")
- (2) 14" X 14" Fuel Doors
- 32"x66" Paddle Handle Door
- Interior Cove Trim Package
- 3" Exterior Trim
- 2 Interior LED Dome Lights w/Wall Switch
- 2 Exterior LED Load Lights w/Wall Switch
- Plastic Salem Vents
- 24" Bright Stoneguard
- Stainless and Aluminum Hardware Kit
- Polished Aluminum Fenders
- Screwless .030" Bonded Side Panels; Two-Tone
- 10000# Coupler w/ 2 5/16" Ball
- 2000# Center Jack
- 7-Way Round Power Connection
- (2) 7800# Safety Chains
- Slide Track Tie-Down System
- (2) Sliding D-Rings, Per Machine
- Limited 4-Year Warranty

### STANDARD SPECIFICATIONS

TRAILER MODEL	PES7x14L-IF Elite	PES7x18L-IF Elite	PES7x22L-IF Elite	PES7x24L-IF Elite
Box WxLxH	82.5"x14"x75"	82.5"x18"x75"	82.5"x22"x75"	82.5"x24"x75"
Interior WxLxHxH	79.5"x13'10"x73"	79.5"x17'10"x73"	79.5"x21'10"x73"	79.5"x23'10"x73"
Overall WxLxH	101"x20'8"x93"	101"x24'8"x93"	101"x28'8"x93"	101"x30'8"x93"
Deck Height	19"	19"	19"	19"
Rear Door Opening WxH	74.5"x69"	74.5"x69"	74.5"x69"	74.5"x69"
Front Door Opening WxH	57" x 69"	57" x 69"	57" x 69"	57" x 69"
Axle(s) - Qty/Rating	2-3500# Braked	2-3500# Braked	2-3500# Braked	2-3500# Braked
Wheels	15" Aluminum	15" Aluminum	15" Aluminum	15" Aluminum
Tires	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	6000#	6000#	6000#	6000#
Curb Weight	1730#	1930#	2005#	2080#
Payload	4270#	4070#	3995#	3920#
Hitch Height	14"	14"	14"	14"