

ENCLOSED INLINE SNOW [INTEGRATED FRAME DELUXE]

STANDARD FEATURES

- All-Aluminum Construction
- Integrated Frame Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x4" Subframe Tubing
- 5/8" Water Resistant Decking
- Leaf Spring Suspension (4" Drop)
- One-Piece Seamless Aluminum Roof
- 12" Water Resistant Kickplate (No Wall Liner)
- Recessed LED Exterior Lighting
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door w/ Spring Assist
- V-Nose Design (60")
- 36"x66" Paddle Handle Door
- Interior Cove Trim Package
- 3" Exterior Trim
- Slide Track Tie-Down System
- (2) Sliding D-Rings, Per Machine
- 2 Interior LED Dome Lights w/Wall Switch
- Plastic Salem Vents
- 16" Bright Stoneguard
- Stainless and Aluminum Hardware Kit
- Polished Aluminum Fenders
- Screwless .030" Bonded Side Panels
(Black, White, Charcoal Standard)
- 10000# Coupler w/ 2 5/16" Ball
- 2000# Center Jack
- 7-Way Round Power Connection
- (2) 7800# Safety Chains
- Limited 4-Year Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	PES7x14L-IF Deluxe	PES7x18L-IF Deluxe	PES7x22L-IF Deluxe	PES7x24L-IF Deluxe
Box WxLxH	82.5"x14"x75"	82.5"x18"x75"	82.5"x22"x75"	82.5"x24"x75"
Interior WxLxHxH	79.5"x13'10"x73"	79.5"x17'10"x73"	79.5"x21'10"x73"	79.5"x23'10"x73"
Overall WxLxH	101"x20'8"x93"	101"x24'8"x93"	101"x28'8"x93"	101"x30'8"x93"
Deck Height	19"	19"	19"	19"
Rear Door Opening WxH	74.5"x69"	74.5"x69"	74.5"x69"	74.5"x69"
Front Door Opening WxH	57" x 69"	57" x 69"	57" x 69"	57" x 69"
Axle(s) - Qty/Rating	2-3500# Braked	2-3500# Braked	2-3500# Braked	2-3500# Braked
Wheels	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod
Tires	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	6000#	6000#	6000#	6000#
Curb Weight	1730#	1930#	2005#	2080#
Payload	4270#	4070#	3995#	3920#
Hitch Height	14"	14"	14"	14"