

UTILITY [FA]

STANDARD FEATURES

- All-Aluminum Construction
- 24" O/C Floor Crossmembers
- 2"X3" Subframe Tubing
- Extruded Aluminum Decking
- Torsion Ride Axle
- Removable Aluminum Fenders
- Fixed 2"X2" Aluminum Side Rail Kit
- Triple Tube Tongue
- Integrated Lay Flat Rear Ramp
- Stake Pockets
- 4-Way Flat Power Connection
- Recessed Rubber Mounted LED Lights
- 6000# Coupler w/ 2" Ball
- (2) 5000# Safety Chains
- Limited 4 Year Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	PU6.5X10FA	PU6.5X12FA	PU6.5x14FA
DECK WxL	76"X118"	76"X142"	76"X166"
OVERALL WxL	102"X14'	102"X16'	102"X18'
DECK HEIGHT	19"	19"	19"
HITCH HEIGHT	15"	15"	15"
DECKING	5/4" PT	5/4" PT	5/4" PT
SURFACE D-RINGS	Optional	Optional	Optional
AXLE(S)-QTY/RATING	1-2200#	1-3500#	1-3500#
WHEELS	14" Aluminum	14" Aluminum	14" Aluminum
TIRES	205/75R15	205/75R15	205/75R15
GVWR	2200#	2990#	2990#
CURB WEIGHT	400#	480#	490#
PAYLOAD	1800#	2510#	2500#